

INTRODUCING

 **Westex**[®]
DH Air[™]

OUR PERFORMANCE AR / FR FABRIC JUST GOT LIGHTER!

Our new, patent pending, Westex[®] DH Air[™] brings all of the great characteristics you've come to love from Westex[®] DH, to a lightweight, Cat 2 fabric.



5.5 oz/yd²



Excellent Performance Characteristics:



Breathability



Moisture Wicking



Color Consistency



Dual Hazard Protection

NFPA 70E Cat 2: 9.1 ATPV
NFPA 2112 Body Burn: 31.7%
(Certification Pending)

WHEN IT COMES TO
FR SAFETY | WE ARE
ALL IN

westex.com

 **WESTEX**[®]
by *Milliken*

Westex® DH

OUR PERFORMANCE AR / FR FABRIC FAMILY IS GROWING!

SUPERIOR BREATHABILITY &
MOISTURE WICKING PERFORMANCE,
NOW IN MORE OPTIONS

Westex® DH Fabrics

STYLE	DESCRIPTION	CONTENT	ARC RATING (cal/cm ²)	NFPA 2112 CERTIFIED (ASTM F1930 Body Burn %)	CUTTABLE WIDTH	SPEC WEIGHT oz/yd ² (g/m ²)	LAUNDRY	TYPICAL GARMENT APPLICATIONS
NEW! 0680/ 0681	4.5 oz Jersey Knit Base Layer	48% Lenzing™ Lyocel, 40% Modacrylic, 12% Aramid	4.7 ATPV	Yes (42.6%)	63"	4.5 (152)		Base Layer Shirt
6800/ 6810	5.5 oz 2x1 Twill	48% Lenzing™ Lyocel, 40% Modacrylic, 12% Aramid	6.6 ATPV	Yes (35.3%)	60"	5.5 (186)		Lightweight Shirts, Vests
6820/ 6830	6.5 oz 2x1 Twill	48% Lenzing™ Lyocel, 40% Modacrylic, 12% Aramid	8.9 ATPV	Yes (16.4%)	60"	6.5 (220)		Lightweight Shirts, Coveralls
6860/ 6870	7.5 oz 2x1 Twill	48% Lenzing™ Lyocel, 40% Modacrylic, 12% Aramid	8.8 ATPV	Yes (13.5%)	60"	7.5 (254)		Shirts, Pants, Coveralls, Jackets
NEW! 6920	8.0 oz 2x2 Canvas	48% Lenzing™ Lyocel, 40% Modacrylic, 12% Aramid	11.0 ATPV	Yes (9.3%)	60"	8.0 (271)		Pants, Coveralls, Jackets
6890	8.5 oz 2x1 Twill	48% Lenzing™ Lyocel, 40% Modacrylic, 12% Aramid	8.8 ATPV	Yes (8.8%)	60"	8.5 (288)		Pants, Coveralls, Jackets

WHEN IT COMES TO
FR SAFETY | WE ARE
ALL IN

westex.com

WESTEX®
by Milliken

PLEASE NOTE: AS EACH CUSTOMER'S USE OF OUR PRODUCT MAY BE DIFFERENT, INFORMATION WE PROVIDE, INCLUDING WITHOUT LIMITATION, TEST RESULTS, RECOMMENDATIONS, SAMPLES, CARE/LABELING/PROCESSING INSTRUCTIONS OR MARKETING ADVICE, IS PROVIDED IN GOOD FAITH BUT WITHOUT WARRANTY AND WITHOUT ACCEPTING ANY RESPONSIBILITY/LIABILITY. ANY TEST RESULTS REPORTED ARE BASED ON STANDARD LABORATORY TESTING BUT SHOULD NOT BE USED TO PREDICT PERFORMANCE IN ACTUAL FIRE SITUATIONS. EACH CUSTOMER MUST TEST AND BE RESPONSIBLE FOR THEIR OWN SPECIFIC USE, FURTHER PROCESSING, LABELING, MARKETING, ETC. ALL SALES ARE EXCLUSIVELY SUBJECT TO OUR STANDARD TERMS OF SALE POSTED AT www.milliken.com/terms (ALL ADDITIONAL/ DIFFERENT TERMS ARE REJECTED) UNLESS EXPLICITLY AGREED OTHERWISE IN A SIGNED WRITING. USE CAUTION NEAR SOURCES OF FLAME OR INTENSE HEAT, AND FOLLOW THE CARE INSTRUCTIONS - DO NOT LAUNDRY WITH BLEACH OR FABRIC SOFTENERS. ANY FR LIFETIME GUARANTEES ARE SUBJECT TO THE LIMITATIONS AND CONDITIONS IN THE FORGOING TERMS OF SALE AND CARE INSTRUCTIONS. Indura®, UltraSoft®, UltraSoft AC®, TrueComfort®, Vinex®, Moda-Quilt®, DH Air™, Synergy®, Indigo®, AllOut®, InsulAir® and CXP® are registered trademarks of Milliken & Company.